

BRITISH TELECOMMUNICATIONS HEADQUARTERS

SPECIFICATION S 1485

FOR

TELEPHONE No. 8756

1 GENERAL.

(a) The Telephone No. 8756 is a Telephone No. 756 with a line cord terminated with an Ambassador-style plug (Plug No. 431A), and with a high impedance bell (Bell No. 59D-1) arranged for parallel connection. It is suitable for the "Newplan" system.

(b) The telephone shall be manufactured in accordance with Specification S 1203D, with amendments as stated in the following paragraphs.

2. CIRCUIT CHANGES

- (a) Omit the straps (Part 2/DLI/20) between T6 & T7, T8 & T9.
- (b) Provide a strap between T17 & T18.
- (c) The bell capacitor (C1) between T7 & T9 may be omitted.
- (d) A Bell 59D-1 (to Specification S 1484) to be fitted in place of a Bell 59C-1.
- (e) Omit the Gas Discharge Tube (Protector 11A)

3. LINE TERMINATION

(a) Omit the Cord Instrument No. 4/121AT colour and the Block Terminal No. 52A colour, and provide a Cord Connecting No. 4/502 light grey 3000 mm.

(b) The spade terminals of the Cord Connecting No. 4/502 ... are terminated within the telephone as follows:-

Red to T8
Blue to T6
Green to T15
White to T18

4. REFERENCES

Specification S 1203D, S 1484.
Drawing DLI/20

END OF SPECIFICATION

ME/PD1.1.1/PJM
August 1981

British Telecommunications Marketing Executive
Product Development (Voice)
PD1.1.1
Proctor House
100/110 High Holborn
LONDON
WC1V 6LD

X24277/ME/PD.