

POST OFFICE TELECOMMUNICATIONS HEADQUARTERS

SPECIFICATION S 4284

FOR

TELEPRAX

1. TABLE OF COMPONENTS

	ITEM	QTY.
	Tele 746F, Modified (see para 2.1)	2
	Cord Inst 4/97 180" with plug 420	2
	Buzzer 32A-3	2
	Dial Centre Label No. 160	2
	STC Diecast Box - DG04300 (see para 3.1)	1
	Jack 84A, Black	2
	Jack 99A	1
	Capacitor No. 7524	2
Ø	Battery, Ever Ready PP1	1
	Connector 1002B	1
	Foam Rubber $\frac{5}{8}$ " x $4\frac{1}{4}$ " x $3\frac{1}{4}$ "	1
	Neoprene Sheet, $\frac{1}{8}$ " x $4\frac{1}{4}$ " x $3\frac{1}{4}$ "	1
	Aluminium Sheet, 14 s.w.g. $3\frac{1}{2}$ " x	1

Ø Proprietary items, to be obtained specially.

2. TELEPHONE INSTRUMENTS

2.1 One Buzzer 32A-3 and a Cord 4/97 180", Grey with plug 420 shall be fitted, and wired in accordance with Diagram SA 4284.

2.2 Telephones will be supplied in any combination of 4 colours (Red, Green, Blue, Yellow), the colour combination being stipulated at the time of ordering, by suffixing the appropriate letters (e.g. SA 4284 ... (R/G) denotes one red and one green telephone).

3. BATTERY BOX

3.1 The battery box should be drilled, engraved and fitted according to Drawing 93265.

3.2 Markings, legends are to be engraved according to Drawing 93265.

4. SCHEDULE OF DRAWINGS, DIAGRAMS, SPECIFICATIONS REFERRED TO IN THIS SPECIFICATION

DRAWINGS	DIAGRAMS	SPECIFICATIONS
93265	SA 4284	-

5. HISTORY

Open Issue January 1972

END OF SPECIFICATION

January 1972
File Ref. J36
THQ/TDD/TD2.5.2

X 21082/TD(Draft)