



NOTES
 1. Position of cable hole altered as shown.
 2. Stile bars reversed.
 3. Strip, Designation No. 8, 16 1/2, overall reduced to 10 5/8 and end reformed.

SCHEDULE		SCREWS, WASHERS ETC.					
ITEM	DESCRIPTION	QTY.	DRG.	QTY.	DESCRIPTION	MATL.	FIN.
A	Buzzer No. 18A	1	8181	2	Wd. Sc. No. 7 x 1 Rd. Hd.	Br.	—
B	Case, Sw. & Ind. D. 9735	1	9735	4	Wd. Sc. No. 10 x 1 1/2 Csk. Hd.	M.S.	Ni.P.Mt.
C	Condenser, M.C. No. 101	8	9208	—	—	—	—
D	Indicator No. 3300A	8	9609	16	Nuts, No. 4 B.A. special for Mtg. No. 130/10A.	—	—
E	" No. 3300B	2	"	4	" " " "	—	—
F	Key No. 68 black	2	60123	—	—	—	—
G	" No. 174 black	1	60128	—	—	—	—
H	" No. 208 yellow	2	60135	—	—	—	—
J	" No. 215 colours see assem.	8	60137	—	—	—	—
K	Key-mounting KE	1	10181	2	Wd. Sc. No. 6 x 1/2 Rd. Hd.	Br.	Blk. Lac.
L	" KY	1	9210	—	—	—	—
M	Mounting No. 130/10A	1	8450	—	—	—	—
N	Relay No. 303A	1	—	—	—	—	—
P	Resistor, Coil No. 12	8	9263	3	Wd. Sc. No. 6 x 2 1/2 Rd. Hd. & Washers No. 6 x 1 1/2 " " " " 2FM.	M.S.	Ni.P.Mt.
Q	Strip, designation No. 8	1	10250	3	Wd. Sc. No. 3 x 1/4 Csk. Hd.	Br.	Blk. Lac.
R	Clip No. 24, 1"	1	60735	—	—	—	—
1/	11091	20	11091	—	—	—	—
10/	11579	1	11579	1	Screw 6 B.A. x 3/4 Ch. Hd. & Nut, Hex.	M.S.	Ni.P.Mt.
1/	11931	1	11931	2	Screw 6 B.A. x 3/8 Ch. Hd. & Nuts, Hex.	"	"
1	—	1	60631	2	Wd. Sc. No. 8 x 1/2 Rd. Hd.	"	"

* To be wrapped in paper and securely tied to each Switch, Indicator.

POST OFFICE ENGINEERING DEPT.
 ENGINEER-IN-CHIEF'S OFFICE.

File Ref. S. 346 Date. 21.1.36

Drawn. Traced. Checked.
[Signatures]

Appr'd. in S Branch

Heid.

Amendment. Suffix.

10063		
SEE SCHED	CB 2057	D 1,000
DRAWINGS	DIAGRAMS.	SPEC'NS.

SWITCH, INDICATOR & KEY, CB2057 8+2/10
 MK. I.

DIAG. CB 2057 REFERS
 SPEC'N. —

SCALE: 1/2

DRG. 60.631

* Printers mounting, to be placed outside trimming line