MASTER

TRIM TO THESE LINES 26" x 29"

S/D.C

DRG SCA/20

POST OFFICE ENGINEERING DEPT.
ENGINEER-IN-CHIEF'S OFFICE S BRANCH
DISTRIBUTION
GENERAL
REFERENCES
DRG. SBU/27 SPEC. SPEC. S116
ASSEMBLY DRG. WIRING DRG.
– –
FILE S.2500 SPEC. –
SCALE 1/1 SIZE 34"
ORIGINAL LIMITS ARE NOT TO BE EXCEEDED SUBJECT TO. –
SUPD IN S SECTION F.J.J DRN ERICSSONS
F. REID. TCD E.A.S.
T.A.C. ITEM CKD T.D.
DATE 14.9.38

AMENDMENT INIT.

FORMERLY DRG. 12929

DIMENSION ·187"r. DELETED FROM SECTION D-D. D.McD. W.A.M. A.E.T.W. 10.1.47	C
RETRACED. PART 1/SBU/27 ADDED. STOCK MADE "M". CORD ENTRY DIM. 570" WAS INCORRECTLY SHOWN AS ·562". D.McD. C.H.S. 10-9-48	D
SECTION G-G ADDED W.A.M. 17-8-51	E
PART 1/SBU/27 DELETED FROM HOLES "C". COLOURS WERE ...,CHINESE RED, JADE GREEN. 20 10 55.	F

SIDE VIEW LOOKING IN DIRECTION OF ARROW 'F'.

SECTION G-G

SECTION A-A.

SECTION B-B.

SECTION C-C.

VIEW LOOKING IN DIRECTION OF ARROW 'E'.

SECTION D-D.

PART	HOLES a	b	c	1/SBU/27 (QTY)	STOCK
1/SCA/20 (COLOUR)	–	–	–	–	M
2/SCA/20 (COLOUR)	1	–	2	2	M
3/SCA/20 (COLOUR)	1	2	2	2	M

NOTES.

1. ·031"r. APPROX REQUIRED ON EDGES AT CHAIN DOTTED LINE. ·016"r. APPROX ON OTHER EXTERNAL CORNERS AND EDGES UNLESS OTHERWISE STATED.
2. MATERIAL & FINISH :- MOULDING MATERIAL, GRADE I., (COLOUR) SPEC S116
3. MATERIAL TO HAVE A MINIMUM THICKNESS OF ·125"
4. "a", "b" & "d" HOLES MUST BE PERPENDICULAR TO PLANE OF BASE.
5. ALL SURFACES AT "X" TO BE SMOOTH

FIRST USE. TELE. No. 332 ETC.

COLOURS :- BLACK, RED, IVORY & GREEN.

STOCK M

FOR GAUGE SEE DRG. 63361

PARTS 1-3/SCA/20 (COLOUR)
(CASE COMBINED SET.)
(1 PIECE)

DRG SCA/20