

Technical Specification

for the EuroRoute 4 Line Dialer

Description	Part Number
EuroRoute 4 Line Dialer	8350-S01-UNV3TX
Connection Box	WBCPo247
Spare Connection Lead	8350-013
Connection Leads (240)	8350-013-240

Description	Part Number
Chaining Cable	8350-036
Chaining Cables (240)	8350-036-240
Printer Cable (10)	8350-030
L Brackets (5)	8350-018

Approvals

Approved for use in Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK.

Approval Number - AA504586 (CE168X).

Specifications	
Dimensions	
Unit Size	275 x 190 x 35 mm
Unit Weight	640 g
PSU Weight	540 g
Shipping Weight	2,000 g
Electrical	
Power	230V +/-10%, 100mA (max)
Temperatures	0-40°C
Humidity	10-90% RH, Non Condensing
Supplied with UK Mains Plug	
Physical	
4 Lines per Unit	
Chain 5 units together (20 lines)	
Line and Power Status LEDs	
Internal Modem - Connect to any Line	
Power fail safe routing to PTT	
Line Types - Loop, Earth	
Dialing Types - MF or Loop Disconnect	

Features
Remote Access
Electronic Serial Number
Call Home Interval Timer (Heartbeat)
Routing Statistics (Peg Count, Minutes)
Programming Password Protection
Central Compatible
Auto Answer - Any Line
Search Facilities
Multiple Country Defaults
1,000+ Search Table Entries
Call Barring Capability
Cost Centre Code & VPN Ability
4 Search Table Sets
Dialing Rules
8 Routes for different Carriers/Call Types
Single Stage Carrier Access (CLI)
Two Stage Carrier Access (PIN)
Detect Line Supervision (Reversal)
Programmable Tone Detection
Callback Capability with Disconnect Codes

Technical Specification

for the EuroRoute 4 Line Dialer

Description	Part Number
EuroRoute 4 Line Dialer	8350-S01-UNVXTX
Connection Box	WBCPo247
Spare Connection Lead	8350-013
Connection Leads (240)	8350-013-240

Description	Part Number
Chaining Cable	8350-036
Chaining Cables (240)	8350-036-240
Printer Cable (10)	8350-030
L Brackets (5)	8350-018

Approvals

Approved for use in Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK.

Approval Number - AA504586 (CE168X).

Specifications	
Dimensions	
Unit Size	275 x 190 x 35 mm
Unit Weight	640 g
PSU Weight	540 g
Shipping Weight	2,000 g
Electrical	
Power	230V +/-10%, 100mA (max)
Temperatures	0-40°C
Humidity	10-90% RH, Non Condensing
Supplied with European Mains Plug	
Physical	
4 Lines per Unit	
Chain 5 units together (20 lines)	
Line and Power Status LEDs	
Internal Modem - Connect to any Line	
Power fail safe routing to PTT	
Line Types - Loop, Earth	
Dialing Types - MF or Loop Disconnect	

Features
Remote Access
Electronic Serial Number
Call Home Interval Timer (Heartbeat)
Routing Statistics (Peg Count, Minutes)
Programming Password Protection
Central Compatible
Auto Answer - Any Line
Search Facilities
Multiple Country Defaults
1,000+ Search Table Entries
Call Barring Capability
Cost Centre Code & VPN Ability
4 Search Table Sets
Dialing Rules
8 Routes for different Carriers/Call Types
Single Stage Carrier Access (CLI)
Two Stage Carrier Access (PIN)
Detect Line Supervision (Reversal)
Programmable Tone Detection
Callback Capability with Disconnect Codes